


typ	max. ztrátový výkon [W]	světlo		pouzdro	typ. světelný tok		vyzař. úhel [°]	typ. úbytek [V]	MC s DPH
		barva	barevná teplota [K] (vlnová délka λp [nm])		[Lm]	při I max [mA]			
OF-HPW-0.5EL	0.5	bílá	6000K	EMITER-A	30	170	130	3.6	45.00
WW-C35SW00H0 SMD	0.5	bílá	6000K	3535 (3.5x3.5mm)	36	200	120	3.2	39.00
WW-C35WW00H0 SMD	0.5	teple bílá	3000K	3535 (3.5x3.5mm)	27	200	120	3.2	39.00
OF-HPWW-0.5EL	0.5	teple bílá	3500K	EMITER-A	26	170	130	3.6	45.00
OF-HPW1-1SL	1	bílá	6000K	STAR-A	72	350	140	3.6	69.00
OF-HPW1-1EL	1	bílá	6000K	EMITER-A	40	350	140	3.6	79.00
OF-HPW3-1EL	1	bílá	6000K	EMITER-A	50	350	140	3.6	89.00
OF-HPW4-1EL	1	bílá	6000K	EMITER-A	60	350	140	3.5	119.00
HPB8-49KW	1	bílá	6000K	EMITER-A	60	350	120	3.6	59.00
WH511N0	1	bílá	6000K	EMITER-D	75	350	120	3.6	59.00
WW-C353W01H0 SMD	1	bílá	6000K	3535 (3.5x3.5mm)	70	350	120	3.6	59.00
WW511N0	1	teple bílá	2900K	EMITER-D	60	350	120	3.6	69.00
WW511T0	1	teple bílá	2900K	EMITER-D	60	350	55	3.6	79.00
WW-C35WW01H0 SMD	1	teple bílá	3000K	3535 (3.5x3.5mm)	70	350	120	3.6	49.00
OF-HPWW3-1EL	1	teple bílá	3500K	EMITER-A	45	350	140	3.6	59.00
OF-HPWW1-1EL	1	teple bílá	3500K	EMITER-A	35	350	140	3.6	52.00
OF-HPWW1-1SL	1	teple bílá	3500K	STAR-A	35	350	140	3.6	59.00
OF-HPB-1SL	1	modrá	(470nm)	STAR-A	8	350	140	3.6	69.00
OF-HPR1-1EL	1	červená	(625nm)	EMITER-A	25	350	140	2.5	59.00
OF-HPR1-1SL	1	červená	(625nm)	STAR-A	25	350	140	2.5	79.00
S12PW6C-B WHT	1.25	bílá	4500K	STAR-B	85	350	120	3.4	75.00
S12PW3C-B WHT	1.4	bílá	4500K	STAR-B	40	400	100	3.5	75.00
S12PW6C WHT	1.4	bílá	6000K	STAR-B	55	350	120	3.4	79.00
S12PW3C WW	1.4	teple bílá	3300K	STAR-B	55	350	120	3.4	75.00
S12N3W6CH WHT	3	bílá	6000K	STAR-B	120	700	120	3.8	115.00
OF-HPW5-3EL	3	bílá	6000K	EMITER-A	105	800	140	3.8	99.00
WH531N0	3	bílá	6000K	EMITER-D	120	700	120	3.9	89.00
WW531N0	3	teple bílá	2900K	EMITER-D	120	700	120	3.9	99.00
WW531T0	3	teple bílá	2900K	EMITER-D	120	700	55	3.9	109.00
S12N3W3C WW	3	teple bílá	3200K	STAR-B	85	700	120	3.8	115.00
HPB8B-49K3YW	3	teple bílá	3300K	STAR-A	105	700	120	3.6	119.00
OF-HPWW1-3EL	3	teple bílá	3500K	EMITER-A	65	800	140	3.8	89.00
OF-HPB-3EL	3	modrá	(470nm)	EMITER-A	13	750	140	3.6	115.00
HPS8-48K3BD	3	modrá	(465nm)	EMITER-E	47	750	160	3.6	95.00
HPS8-48K3BD/WPC	3	modrá	(465nm)	STAR-E	47	750	160	3.6	109.00
W42182-U	4	bílá	6300K	STAR-A	100	1000	127	3.3	99.00
AW3231	4	bílá	6300K	šestiúh. 30mm	240	20	130	napáj. napětí 230VAC	349.00
AN3231	4	teple bílá	3000K	šestiúh. 30mm	160	20	130		349.00
OF-HPW-5EL	5	bílá	6000K	EMITER-A	175	1200	140	3.6	199.00
HPR8C-49K5WF	5	bílá	6000K	EMITER-C	262	1400	110	3.8	169.00
HPR8C-49K5WF/WPCB	5	bílá	6000K	STAR-C	262	1400	110	3.8	189.00
HPB8B-49K5YW	5	teple bílá	3300K	STAR-A	195	1200	120	3.6	189.00
HPR8C-49K5YWF	5	teple bílá	3300K	EMITER-C	232	1400	110	3.8	179.00
HPR8C-49K5YWF/WPCB	5	teple bílá	3300K	STAR-C	232	1400	110	3.8	179.00
OF-HPWW-5SL	5	teple bílá	3500K	STAR-A	170	1200	140	3.6	219.00
HPR8F-4K3RGB/W	3x 1	RGB	(625/525/465)	STAR-X	45/55/16	3x 350	110	2.3/3.6/3.6	159.00
OF-HPRGB-1SL	3x 1	RGB	(620/525/465)	STAR-A	28/50/7	3x 350	140	2.4/3.4/3.4	149.00
W724C0	10	bílá	6300K	P7 (ø12mm)	800	2800	130	3.6	499.00




STAR-A




AN(AW)3231



EMITER-A



P7 (ø12mm)



3535
(3.5x3.5mm)



EMITER-D